

**DECLARATION OF PERFORMANCE**  
ASESA-No. 029CPR2013-07-01

1. Unique identification code of the product-type: **Hard paving grade bitumen 10/20**
2. Intended use: **Construction and maintenance of roads, airfields and other paved areas**
3. Manufacturer: **ASFALTOS ESPAÑOLES S. A. (ASESA)**  
PO Box 175  
43080 Tarragona, Spain  
Tel. +34977553073  
E-mail: [asesa@asesa.es](mailto:asesa@asesa.es)
4. Authorised representative: **no authorised representative**
5. System of assessment and verification of constancy of performance (AVPC): **System 2+**
- 6.a Harmonised standard: **EN13924:2006**

Notified bodies: **nº 0120 SGS United Kingdom Ltd.**  
**performed the initial inspection of the factory and the factory production control**

**nº 0099 AENOR INTERNACIONAL, S.A.U**  
**performed the last assessment and evaluation of the factory production control**

7. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Consistency at intermediate service temperature	Class 3 (10 to 20) x 0,1 mm	5.1.2 of EN 13924:2006 (Penetration at 25°C)
Consistency at elevated service temperature	Class 4 (60 to 70) °C	5.1.3 of EN 13924:2006 (Softening point)
Durability of the consistency at intermediate and elevated service temperatures	Class 2 ≤ 0,5 % ≥ 55 % ≤ 10 °C (-1,5 to +0,7)	5.1.4 of EN 13924:2006 (Change of mass) (Retained penetration) (Increase in softening point and Penetration Index on unaged bitumen)

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Francisco Claver Rodrigo**  
General Director of ASES A